## What is claimed is:

5

10

15

- 1. A structure for wiring a wiring harness for an automobile between an electronic control unit and one or more devices, the automobile having a steering member extended from a driver's seat side of the automobile to an assistant's seat side of the automobile, a control module arranged at a center in a width direction of the steering member and an electronic control unit for controlling the devices arranged at the assistant's seat side of the steering member and a plurality of units arranged at the driver's seat side, the structure comprising:
  - a housing member including;
    - a first portion having a first connector for connection with the devices;
    - a second portion housing the electronic control unit; and
      - a third portion being formed in a slim shape and interconnecting the first portion and the second portion; and
- a wiring harness housed in the third portion, the wiring
  harness interconnecting the first connectors and the electronic
  control unit,

wherein the housing member is arranged along the steering member in a manner that the third portion is housed between the control module and the steering member.

25 2. The structure of claim 1, wherein the control module controls a heater, a ventilator, an air-conditioner and distribution doors.

- 3. The structure of claim 1, wherein the electronic control unit comprises a second connector mating with the first connector, an amplifier for a meter and an air-conditioner control amplifier.
- 5 4. The structure of claim 1, wherein the first portion comprises a plurality of first connectors for connection with the devices and the control module is arranged between the first portion and the second portion.
- 5. The structure of claim 4, wherein the first connectors are formed in a unified shape having a unified terminal alignment and connected with a power bus circuit and a superimposing communication unit of the electronic control unit.
  - 6. The structure of claim 1, wherein the third portion is so dimensioned as to be insertable in space formed between the control module and the steering member.

15